



## AMP 4x120

- 24V emergency power supply
- 4 channels
- 230V and 115V operation

The 4-channel power amplifier AMP 4 x 120 is specially designed for the application in public buildings, schools or coliseums.

The amplifier with 4 x 120 Watt is protected against overload and short circuit. A fan provides for thermal stability. The output level is shown by a LEDVU meter. With the speaker outputs of 70 Volt, 100 Volt and 8 Ohm the AMP 4 x 120 can be recommended for all kinds of installation condition.

1x XLR, 1 x 1/4 inch jack and 2 x cinch connectors for incoming signals are available for each channel. The 19-inch housing (3U) allows for space-saving mounting in racks.

## Technical Data

|                       |   |
|-----------------------|---|
| Description           | AMP 4x120   |
| Power (Max/Rated)     | 4 x 120 W   |
| Inputs                | Line input: 1V, 47Kohm symmetrisch, unsymmetrisch, balanced, unbalanced |
| Frequency response    | 50Hz<br>50~20KHz $\pm$ 3 dB   |
| Outputs               | 8ohm, 100V (70V/100V selectable)  |
| THD                   | Less than 1% at 1 KHz, rated power                                      |
| Mains/Battery Voltage | AC 230V/240V 50/60Hz<br>DC 24V (MAX 10% deviation)                      |
| Power consumption     | 1100 W  |
| Colour                | black   |
| Dimensions            | 133x483x380 mm  |
| Weight (net)          | 25,70 kg  |
| Packing Unit          | 1   |
|                       | 24 volt   |

## Product Attributes



Measurements according to DIN IEC 268-5



**Article Nr.:**

80000050

**Packing Unit:**

1

